

# 10LE8

## Twin Dual-Control Pentode

The 10LE8 is the same as the 6LE8 except for:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	10	V
Warm-up time (Average). . . . .	11	s

# 11AR11

## Semiremote-Cutoff Twin Pentode

### DUODECAR TYPE

The 11AR11 is the same as the 6AR11 except for:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	11.2	V
Warm-up time (Average). . . . .	11	s

# 11CY7

## Dual Triode

### With High-Mu Unit and Low-Mu Unit

The 11CY7 is the same as the 6CY7 except for:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	11.0	V
Warm-up time (Average). . . . .	11	s

# 11DS5

## Beam Power Tube

The 11DS5 is the same as the 6DS5 except for:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	11.2	V
Warm-up time (Average). . . . .	11	s

