


Full-Wave Vacuum Rectifier

The 5Y4GT is the same as the 5Y4GA except for the following items:

Mechanical:

Operating Position.	Vertical, base down or up, or Horizontal with pins 2 and 3 in vertical plane
Maximum Overall Length.	3-3/8"
Maximum Seated Length.	2-13/16"
Maximum Diameter.	1-9/32"
Dimensional Outline.	See <i>General Section</i>
Bulb.	T9
Base.	Intermediate-Shell Octal 6-Pin, Arrangement 1 (JEDEC Group 1, No. B6-8), or Short Intermediate-Shell Octal 6-Pin with External Barriers, Arrangement 1 (JEDEC Group 1, No. B6-60)
Basing Designation for BOTTOM VIEW.	5Q

Pin 1 - No Connection
Pin 2 - No Connection



Pin 3 - Plate No. 2
Pin 5 - Plate No. 1
Pin 7 - Filament
Pin 8 - Filament

5Z3


Full-Wave Vacuum Rectifier

The 5Z3 is the same as the 5U4G except for the following items:

Mechanical:

Operating Position.	Vertical, base down or up, or Horizontal with pins 1 and 4 in horizontal plane
Maximum Overall Length.	5-3/8"
Base.	Medium-Shell Small 4-Pin (JEDEC No. A4-9)
Basing Designation for BOTTOM VIEW.	4C

Pin 1 - Filament
Pin 2 - Plate No. 2



Pin 3 - Plate No. 1
Pin 4 - Filament

