

RADIOTRONICS

TECHNICAL BULLETINS, 1939

I N D E X

	Page
Amplifier, with Negative Feedback over 3 stages; possible causes of Parasitics (A145B)	43
Amplifier, 13.5 Watts, using 2A3's (A503)	48
Attenuation, High Frequency, due to Shunt Capacitance	4
Attenuation, High Frequency, due to Shunt Correction	54
Attenuation, Low Frequency, due to Grid Coupling Condenser	60
Attenuation, Low Frequency, due to Screen Bypassing	34-35
A.V.C. Curves, Two Methods for	41-43
Bantam Valves, 1.4 Volt	56
Bass Boosting, with Pickup, Filter for	62
Battery Valves, 1.4 Volt, in Battery/A.C. Receivers	63
Bias, Grid Leak	3
Blocking, Grid, to avoid with 6K8-G	25
Bypassing, Screen, Formula for	34
Capacitances, Shunt, Effect of	4
Cathode Ray Tubes, Interchangeable	14
Coils for 2 Volt Battery Receiver (1C7-G)	25-26
Coils for 6K8-G	38
Converter Valve, Application of 6SA7	8
Crystal Microphones, see under "Microphones".	
Distortion, see under "Harmonic Distortion".	
Dropping Resistors, see under "Resistors".	
Filament Voltage Limits	6, 22, 32
Filter for Bass Boosting, with Pickup	62
Flutter, Method for Reduction of	22
Gaseous Voltage Regulators, Use of	35
Grid Bias Voltage, Limits of	33
Grid Blocking, with 6K8-G, To avoid	25
Grid Circuit Impedance for Microphone Pre-amplifiers	21
Grid Coupling Condenser, Attenuation due to	60-61
Grid Current, Oscillator, Limits of	26-27
Grid Leak Bias	3
Grid Leak Bias, Receiver using	39-43
Grid Resistors, Maximum Values of	33
Harmonic Distortion, Third, Graphical Method for	2
Heater Voltage, Limits of	32-33
Hum, Two Causes and their Diagnosis	22
I.F. Amplifier, using 6SK7, etc. (R.C.A. Application Note)	51-53
Input Loading of Receiving Valves (R.C.A. Application Note)	15-19
Intermediate Frequency, Standard	67
Inverse Feedback, see under "Negative Feedback".	
Kinescope, Definition of	14
Maximum Ratings, see under "Ratings".	
Microphone Amplifier, Resistance in Grid Circuit	21
Mounting Position, 1.4 Volt Series	25
Negative Feedback:	
Parallel Feedback Circuit	5
Feedback over three stages, Possible causes of Parasitics with	43

Oscillator Grid Current Limits	26-27
Parasitics with Negative Feedback over three stages, Possible causes of	43
Phase Splitter, Low Impedance, using 6V6-G as Triode	48
Pickup, Filter for Bass Boosting with	62
Pickup, Switching Method in Receiver	41
Plate Voltage, Limits of	32-33
Radiotron Designer's Handbook	59
Ratings, Dual, for Transmitting Valves	67
Ratings, Maximum, Significance of	32-33
Receiver, A.C., Tuner Unit for (R201)	50
Receiver, A.C., 5 valve Simple (RD44)	39-43
Receiver, Battery, 5 Valve Vibrator (A58)	24
Receiver, Battery, 5 Valve, 2 Volt (A59)	25
Receivers, Battery/A.C., Use of 1.4 Volt Valves in	63
Resistance Coupled Amplifier, Attenuation due to Grid Coupling Condenser in	60-61
Resistance in Grid Circuit of Microphone Pre-amplifier	21
Resistors, Screen Dropping; Restrictions with Super-control Valves	21
R.F. Amplifier Valves, Input loading of (R.C.A. Application Note)	15-19
R.F. Amplifier Valves, Limited Grid Input Voltage with Super-control Characteristics	45
Screen Dropping Resistors, Restrictions with Super-control Valves	21
Screen Bypassing, Formula for	34
Screen Voltage, Limits of	33
Shunt Capacitances, Effect of (see also below)	4
Shunt Capacitances, Corrected Data	54
Super-control Characteristics, Limited Grid Input Voltage with	45
Tone Control, Continuously Variable	41
Tone Control, Three Position	41
Transmitting Valves, Australian made	54
Valve Type Numbers, Meaning of Suffixes	64
Voltage Regulators, Gaseous, Use of	35
1A7-G Mounting Position	46
1A7-GT, Announcement	46
Mounting Position	46
1C7-G Shortwave Operation	6
Used in Receiver	24-25
1D8-GT Announcement	46
Data	55
1F5-G Maximum Grid Resistor	33
1G4-G Announcement	22
Data	36
Mounting Position	46
1G5-G Maximum Grid Resistor with	33
1G6-G Announcement	22
Data	36-37
Mounting Position	46
1H5-GT Announcement	46
Mounting Position	46
1K7-G Used in Receiver	24-25
1L5-G Maximum Grid Resistor with	33
Used in Receiver	24-25
1M5-G Used in Receiver	24-25
1N5-GT Announcement	46
Mounting Position	46
1Q5-GT Announcement and Data	46
Mounting Position	46
1T5-GT Announcement	70
Data	63
2A3 Application	48
Maximum Grid Resistor with	33
2V3-G Announcement and Data	14
2X2/879 Announcement	46
Data	53
3AP1/906-P1 Announcement	46
3AP4/906-P4 Announcement	46
3Q5-GT Announcement	70
Data	64
5AP4/1805-P4 Announcement	58
5BP1/1802-P1 Announcement	46
5BP4/1802-P4 Announcement	46
5U4-G Application	48

5V4-G	Note on Characteristics	37
5Y3-G	Use in Receiver	39-43
6A8	Input Loading	16
6A8-G	Use in Receiver	39-43
6A8-GT	Announcement	6
6AB7/1853	Announcement	38
6AC7/1852	Announcement	38
6AE5-GT	Announcement	70
6AG7	Announcement	46
	Data and Application	65
6B6-G	Grid Leak Bias	3
	Use in Receiver	39-43
	With Parallel Feedback	5
6B8-G	With Parallel Feedback	5
6F5-GT	Announcement	38
6F6-G	Maximum Grid Resistor with	33
	Use in Receiver	39-43
6G8-G	Dropping Resistor for	21
6J5-GT	Announcement	38
6J7	Input Loading of	16
6J7-G	Application	48
	With Parallel Feedback	5
6J7-GT	Announcement	38
6K6-GT	Announcement	38
6K7	As I.F. Amplifier	51-53
	Input Loading of	16
6K7-GT	Announcement	6
6K8-G	Coils for	38
	Heater Voltage of	33
	Oscillator Grid Current Limits	26-27
	To Avoid Grid Blocking with	28
6L6-G	Maximum Grid Resistor with	33
6L7	Input Loading of	16
6P5-G	Announcement	70
6Q7-G	Parallel Feedback with	5
6Q7-GT	Announcement	6
6SA7	Announcement	6
	Data and Application (R.C.A. Note)	8-12, 14
	Input Loading of	16
6SC7	Announcement	6
	Data	14
6SJ7	Input Loading of	16
6SK7	Input Loading of	16
	I.F. Amplifier using (R.C.A. Note)	51-53
6U5	In place of 6G5	6
6U5/6G5	Announcement	6
6U7-G	Dropping Resistors for	21
	Improved Stability with	58
	Use in Receiver	39-43
6V6-G	Heater Voltage of	33
	Maximum Grid Resistor with	33
	Triode Operation	48, 50
6V6-GT	Announcement	58
6Y6-G	Revised Characteristics	46
7A6	Announcement	70
7A7	Announcement	70
7A7-LM	Announcement	70
7A8	Announcement	70
7AP4	Announcement	70
7B7	Announcement	70
7C6	Announcement	70
7Y4	Announcement	70
9AP4/1804-P4	Announcement	46
12A8-GT	Announcement	6
12AP4/1803-P4	Announcement	46
12C8	Announcement	30
12F5-GT	Announcement	70
12J5-GT	Announcement	70
12J7-GT	Announcement	38
12K7-GT	Announcement	6
12Q7-GT	Announcement	6
12SA7	Announcement	30
12SC7	Announcement	30
12SF5	Announcement	30
12SJ7	Announcement	30
12SK7	Announcement	30
12SQ7	Announcement	30
25AC5-GT	Announcement	70

25L6-GT	Announcement	6
25Z6-GT	Announcement	6
35A5	Announcement	70
35A5-LT	Announcement	70
35L6-GT	Announcement	30
35Z3	Announcement	70
35Z3-LT	Announcement	70
35Z4-GT	Announcement	30
35Z5-GT	Announcement	38
45	Maximum Grid Resistor with	33
45Z5-GT	Announcement	70
50	Maximum Grid Resistor with	33
50L6-GT	Announcement	46
75	With Grid Leak Bias	3
	With Parallel Feedback	5
83V	Note on Characteristics	37
VR105-30	Application	35-36
VR150-30	Application	35-36
806	Photograph	23
807	Data with Photograph	31
809	Data	7
810	Photograph	1
811	Announcement	70
	Data	67
	Photograph	68
812	Announcement	70
	Data	67
828	Announcement	70
	Data with Photograph	69
833	Data with Photograph	29
893	Announcement	46
	Data	68
899	Announcement	70
	Data	68
903	Deleted from List	70
	Note on Interchangeability	14
905	Note on Interchangeability	14
906	Note on Interchangeability	14
906-P4	Note on Interchangeability	14
907	Note on Interchangeability	14
908	Note on Interchangeability	14
909	Note on Interchangeability	14
910	Note on Interchangeability	14
911	Deleted from List	70
924	Announcement	58
	Photograph	58
925	Announcement	58
926	Announcement	58
927	Announcement	58
954	Input Loading	16
957	Announcement	6
	Data	20, 30
958	Announcement	6
	Data	20, 30
959	Announcement	6
	Data	20, 30
1616	Data	2
1620	Announcement	30
	Data	27
1621	Announcement	30
	Data	27-28
1622	Announcement	30
	Data	28
1623	Data	7
1624	Announcement	46
	Data (see also below) with Photograph	56-57
	Correction to Data	68
1803-P4	Announcement	14
1804-P4	Announcement	14
1849	Announcement	38
1850	Announcement	38
1851	Input Loading	16
1852	Input Loading	16
1853	Input Loading	16
1898	Announcement	70
2050	Announcement	46
	Data	37
2051	Announcement	46
	Data	44-45