

Specification MOS/CV4002 Issue 5 Dated 6 March 1957 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

—————> Indicates a change

TYPE OF VALVE - Reliable Pentode with flexible leads CATHODE - Indirectly heated ENVELOPE - Glass PROTOTYPE - CV138 EQUIVALENT FINNED VALVE - CV4014  <u>RATING, CONNECTIONS, CAPACITANCES AND NOTES</u> See Specification MOS/CV4014, Issue 4 Dated 5.11.56	<u>MARKING</u> See K1001/4		
	<u>BASE</u> B7G/F		
	<u>DIMENSIONS</u> See K1001/41/D11		
	Dimension (mm)	Min	Max
	A Seated height	-	47.5
B Diameter	16.0	19.0	
D Lead length	38	-	
<u>MOUNTING POSITION</u> Any			

#### TESTS

→ The tests required by specification MOS/CV4014, Issue 4 dated 5.11.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u> DELETE -						
7.2	Base Strain ADD -	No voltages	6.5	IA			
5.12	Lead Fragility	No voltages	6.5	IA			