

Specification MOS/CV4065 Issue 2 Dated 23 Nov 1956 To be read in conjunction with K1001, BS448 and BS1409	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

TYPE OF VALVE - Reliable Low Impedance Pentode with flexible leads. CATHODE - Indirectly-heated ENVELOPE - Glass EQUIVALENT PINNED VALVE - CV 4062	<u>MARKING</u> K1001/4		
	<u>BASE</u> B7G/F		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4062, issue 2 dated 23 Nov 1956	<u>DIMENSIONS</u> See K1001/A1/D11		
	Dimensions (mm)	Min	Max
	A. Seated height	-	63.5
	B. Diameter	16	19
	D. Lead Length	38	-
	<u>MOUNTING POSITION</u> Any		

TESTS

The Tests required by specification MOS/CV4062, issue 2 dated 23 Nov 1956 shall be performed except as follows :-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u> DELETE -						
→ 7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			