

VALVE ELECTRONIC

CV4107

Specification MOA/CV4107 Issue 1 dated 24.1.61 To be used in conjunction with K1001 BS448 and BS1409	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

indicates a change

<p>TYPE OF VALVE - Reliable low noise R.F.Triode with Gold plated pins.</p> <p>ENVELOPE - Glass unmetallised</p> <p>CATHODE - Indirectly heated</p> <p>PROTOTYPE - A2913, CV4081</p>	<p><u>MARKING</u></p> <p>See K1001/4</p>							
<p style="text-align: center;"><u>RATINGS, CONNECTIONS, CAPACITANCES AND NOTES</u></p> <p>See specification MOS/CV4081</p> <p>Issue 1A dated 9th August, 1959</p>	<p><u>BASE</u></p> <p>B7G</p>							
	<p><u>DIMENSIONS</u></p> <p>See K1001/A1/D11</p>							
	<p><u>MOUNTING POSITION</u></p> <p>Any</p>							
<p><u>TESTS</u></p> <p>The tests required by Specification MOS/CV4081 Issue 1A dated 9th August, 1959 shall be performed except as follows:-</p>								
K1001	TEST	TEST CONDITIONS	AQL	Insp. Level	Symbol	Limits	Units	Notes
	<u>GROUP E</u> <u>DELETE:-</u>							
5.12.	Lead Fragility	No Voltages	6.5	IA				
	<u>ADD:-</u>							
7.2	Base Strain	No Voltages	6.5	IA				
<p>JOINT SERVICE CATALOGUE NUMBER. 5960-99-037-2350</p>								

CV4107/1/1