

3AU6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

The 3AU6 is the same as the 6AU6A except for:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	A
Voltage (AC or DC) at heater amperes = 0.600	3.15	V
Warm-up time (Average)	11	s

3AV6

Twin Diode—High-Mu Triode

7-PIN MINIATURE TYPE

The 3AV6 is the same as the 6AV6 except for:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	A
Voltage (AC or DC) at heater amperes = 0.600	3.15	V
Warm-up time (Average)	11	s

3BA6

Remote-Cutoff Pentode

The 3BA6 is the same as the 6BA6 except for:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	A
Voltage (ac or dc) at 0.600 A	3.15	V
Warm-up Time (Average).	11	s

3BN4A

Medium-Mu Triode

The 3BN4A is the same as the 6BN4A except for:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	A
Voltage (ac or dc) at 0.450 A	3	V
Warm-up Time (Average).	11	s

3BN6

Beam Tube

The 3BN6 is the same as the 6BN6 except for:

Heater Characteristics and Ratings:

Current	0.600 \pm 0.040	A
Voltage (ac or dc) at 0.600 A	3.15	V
Warm-up Time (Average).	11	s

3BU8/3GS8

Sharp-Cutoff Twin Pentode

With Common Cathode

Grid No. 1, and Grid No. 2

The 3BU8/3GS8 is the same as the 6BU8 except for:

Heater Characteristics and Ratings:

Current	0.600 \pm 0.040	A
Voltage (ac or dc) at 0.600 A	3.15	V
Warm-up Time (Average).	11	s