

## Diode—Sharp-Cutoff Pentode

With Heater Having Controlled Warm-Up Time

## GENERAL DATA

## Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC) . . . . .	6.3 <sup>a</sup>	6.3 ± 0.6	volts
Current . . . . .	0.450 ± 0.030	0.450 <sup>b</sup>	amp
Warm-up time (Average) . . . . .	11	-	sec
Peak heater-cathode voltage (Each unit):			
Heater negative with respect to cathode . . . . .	200	max.	volts
Heater positive with respect to cathode . . . . .	200 <sup>c</sup>	max.	volts

Direct Interelectrode Capacitances:<sup>d</sup>

## Diode Unit:

Plate to cathode and heater . . . . .	2.4	μμf
Cathode to plate and heater . . . . .	3.0	μμf

## Pentode Unit:

Grid No.1 to plate . . . . .	0.015	max.	μμf
Grid No.1 to cathode, grid No.3 & internal shield, grid No.2, and heater . . . . .	7.0		μμf
Plate to cathode, grid No.3 & internal shield, grid No.2, and heater . . . . .	3.2		μμf
Diode plate to pentode grid No.1 . . . . .	0.005	max.	μμf
Diode cathode to pentode plate . . . . .	0.15	max.	μμf
Diode plate to pentode plate . . . . .	0.035	max.	μμf

Characteristics, Class A<sub>1</sub> Amplifier:

Plate Supply Voltage . . . . .	125	volts
Grid No.3 . . . . .	Connected to cathode at socket	
Grid-No.2 Supply Voltage . . . . .	125	volts
Cathode Resistor . . . . .	56	ohms
Plate Resistance (Approx.) . . . . .	0.2	megohm
Transconductance . . . . .	9300	μmhos
Plate Current . . . . .	11.5	ma
Grid-No.2 Current . . . . .	3.6	ma
Grid-No.1 Voltage (Approx.) for plate μa = 20 . . . . .	-6	volts
Grid-No.1 Voltage (Approx.) for plate ma = 2, and cathode resistor (ohms) = 0 . . . . .	-3	volts

## Mechanical:


Operating Position . . . . .	Any
Type of Cathodes . . . . .	Coated Unipotential
Maximum Overall Length . . . . .	2-3/16"
Maximum Seated Length . . . . .	1-15/16"
Length, Base Seat to Bulb Top (Excluding tip) . . . . .	1-9/16" ± 3/32"



# 6HJ8

Diameter. . . . . 0.750" to 0.875"  
Dimensional Outline . . . . . See *General Section*  
Bulb. . . . . T6-1/2  
Base. . . . . Small-Button Noval 9-Pin (JEDEC No. E9-1)  
Basing Designation for BOTTOM VIEW. . . . . 9CY

Pin 1 - Pentode  
Cathode  
Pin 2 - Pentode  
Grid No. 1  
Pin 3 - Pentode  
Grid No. 2  
Pin 4 - Heater  
Pin 5 - Heater  
Pin 6 - Pentode Plate



Pin 7 - Diode  
Cathode  
Pin 8 - Diode  
Plate  
Pin 9 - Pentode  
Grid No. 3,  
Internal  
Shield

## PENTODE UNIT — Class A<sub>1</sub> Amplifier

### Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE . . . . . 330 max. volts  
GRID No. 3 (SUPPRESSOR  
GRID) . . . . . *Connect to cathode at socket*  
GRID-No. 2 (SCREEN-GRID) SUPPLY VOLTAGE. . . 330 max. volts  
GRID-No. 2 VOLTAGE . . . . . *See Grid-No. 2 Input Rating Chart*  
*at front of Receiving Tube Section*  
GRID-No. 1 (CONTROL-GRID) VOLTAGE:  
Positive-bias value . . . . . 0 max. volts  
GRID-No. 2 INPUT:  
For grid-No. 2 voltages up to 165 volts. . . 0.55 max. watt  
For grid-No. 2 voltages between 165  
and 330 volts . . . . . *See Grid-No. 2 Input Rating Chart*  
*at front of Receiving Tube Section*  
PLATE DISSIPATION . . . . . 3.2 max. watts

### Maximum Circuit Values:

Grid-No. 1-Circuit Resistance:  
For fixed-bias operation. . . . . 0.25 max. megohm  
For cathode-bias operation. . . . . 1 max. megohm

## DIODE UNIT

### Maximum Ratings, Design-Maximum Values:

DC PLATE CURRENT. . . . . 5 max. ma

### Characteristics, Instantaneous Value:

Plate Current for plate volts = 10. . . . . 50 ma

<sup>a</sup> At heater amperes = 0.450.  
<sup>b</sup> At heater volts = 6.3.  
<sup>c</sup> The dc component must not exceed 100 volts.  
<sup>d</sup> without external shield.

