



Engineering Data

Bulletin E-162
Page 1 of 2 pages

October 5, 1950

HYTRON TYPE 600L

MECHANICAL DATA

Coated filament		
Outline drawing		Bulb T-9
Base	B5-10 Intermediate shell octal 5-pin	
Maximum diameter		1.5/16"
Maximum overall length		1.1/16"
Maximum seated height		
Pin connections		Basing 5T
Pin 1 - No connection	Pin 6 - No connection	
Pin 2 - Filament	Pin 8 - Filament	
Pin 4 - No connection	Cap Plate	
	Cap Plate	
Cap		See drawing
Mounting position		Vertical*

* Horizontal operation permitted if pins #2 and #4 are in vertical plane.

ELECTRICAL DATA

Ratings

Filament voltage (ac or dc)	5.0	volts
Maximum peak inverse voltage	3200	volts
Maximum steady state peak plate current each plate	375	ma
Maximum transient peak plate current each plate	1.4	amperes
Tube voltage drop (measured with tube conducting 145 ma each plate)	50	volts

Typical operation (Full Wave Rectifier)

	<u>Capacitor Input</u>
Filament voltage	5.0 volts
Filament current	2.0 amperes
AC plate supply voltage each plate	375 volts
Input condenser	4 uf
Effective plate supply impedance each plate	60 ohms
DC output current	120 ma
DC output voltage	360 volts

