


Current Equipment Type

TYPE C17HM/1
B12A (DUODECAL)
BASE



The C17HM/1 is a wide angle Teletube with a tetrode gun, ion trap, aluminized screen, and external conductive coating, for use in television picture monitors and similar applications. This tube is manufactured to a strict specification and is capable of providing high-grade pictures for television monitoring and industrial purposes.

RATINGS

Heater Voltage	6.3 volts
Heater Current	0.6 amps.
Final Anode Voltage (V_{a2})	16 kilovolts max.
Final Anode Voltage (V_{a2})	14 kilovolts min.
First Anode Voltage (V_{a1})	410 volts max.
First Anode Voltage (V_{a1})	250 volts min.
Beam Current	250 μ A max.
Grid Voltage (V_g)	-2 volts max.
Peak Heater—Cathode Voltage (V_{hk})	180 volts max.
Peak Heater—Cathode Voltage (V_{hk})†	410 volts max.
Diagonal Deflection Angle	70° approx.

†Heater negative with respect to cathode and only during a warm-up period not exceeding 15 seconds

OPERATING CHARACTERISTICS

Final Anode Voltage	16 kilovolts
First Anode Voltage	300 volts
Peak to Peak Modulation for Beam Current of 150 μ A	30 volts
Grid Voltage limits for Spot Cut-off	-55 to -77 volts
Field Strength of Ion-Trap Magnet	45 gauss approx.

INTER-ELECTRODE CAPACITANCES

Grid to all	9.0 pF max.
Cathode to all	6.0 pF max.
Final Anode to External Coating	1,500 pF max.

NOTES:

1. The ion trap should be adjusted to give the brightest picture. Failure to do this may shorten the life of the tube.
2. The spot shape depends to some extent upon the ion-trap magnet. A suitable type is the integral moulded ring type which is magnetised at opposite ends of a diameter and gives a more uniform field than types using a single magnet with pole pieces.